

The new self-propelled AFTraction trencher with unique rubber tracks is ideal for any landscaping project - irrigation, drainage, cables, curb stones, etc.

This is a very easy trencher to operate, with two speed settings and the flexibility of moving left and right without any fuss.

Weight displacement is excellent with wide rubber tracks supporting the weight of the trencher.

www.trenchers.co.uk Telephone: +44 (0)1787 311811 E-mail: info@trenchers.co.uk



The AFTraction digs to a maximum of 24 inches with a trench width of 6 inches. All trencher functions are in easy grasp of the operator who never has to leave his position on the footplate, located behind the trencher.

The digging boom with chain and trench cleaner is hydraulically controlled to easily vary trench depths. The chain is equipped with mixed soil blades and bullet teeth.

Technical Characteristics:

Engine:	Honda 390 GX 13HP
Digging depth:	Adjustable up to 24'' (60 cm)
Trench width:	Adjustable up to 6'' (16 cm)
Soil evacuation:	Auger to move earth to the
	side of the trench
Trencher dimensions:	Overall length 59'' x width 28''
Weight:	280 kg



Rubber tracks



Soil evacuation with auger

Bullet teeth



Chain with mixed soil blades and bullet teeth



www.trenchers.co.uk

Our policy is one of continuous improvement, and we reserve the right to change specification of equipment without notice. **TD** Illustrations do not necessarily show products to current specifications