

With constantly increasing demands on sports turf in the leisure and professional sectors, optimum pitch or playing surface condition is paramount. Intensive drainage is considered to be an important measure taken to both enhance turf condition and cope with today's demands.



WIZZ WHEEL 75



WIZZ WHEEL 75

Through increasing demand for a more flexible machine, the AFT 75 Wizz Wheel is capable of both digging and grading main drains up to 750mm deep and 125mm wide, together with gravel banding or sand slitting as narrow as 50mm. The more compact Wizz Wheel 55 is used by many golf clubs looking to incorporate a large amount of intensive sand slitting or gravel banding into existing main drains.



WIZZ WHEEL 55

AFT Trenchers offers two powerful tractor mounted, PTO driven slit trenchers. These machines have been proven to be the ultimate solution to a fast, clean and cost effective means of installing and maintaining intensive drainage systems by leading golf clubs and contractors world wide.



WIZZ WHEEL 75

A.F.T. TRENCHERS LIMITED

Edgworth Road, SUDBURY, Suffolk CO10 2TG

Telephone: 01787 311811 • Fax: 01787 310888 email: info@trenchers.co.uk • www.trenchers.co.uk

KEY FEATURES 55 & 75









- High speed trenching up to 2000 metres per hour - means reduced labour costs.
- Tractor mounted for ease of manoeuvrability and lower unit costs when compared to a self propelled machine.
- Direct drive from the PTO-shaft offers maximum torque, reliability and minimum ware and maintenance.
- Pocket mounted reversible digging blades fixed in by roll pins for ease of re-placement.
- Two different systems of tungsten carbide digging teeth for operation in hard and stoney conditions.
- A large removable side panel allows for fast access for easy cleaning.
- Continuously variable hydraulic depth control can be linked to a laser for grading.
- The soil clear-up system completely removes all soil even in wet and sticky conditions and elevates it into a vehicle running alongside.
- Adjustable staggered twin discs pre-cut the turf and contribute to minimum ground disturbance.
- Option for pipe laying chutes.

	WIZZ WHEEL 55	WIZZ WHEEL 75
Number of pockets	10	12
Maximum digging depth	550mm	750mm
Width availability	50, 70, 95, 125mm	50, 70, 95, 125mm
Rear crumber set up	Floating self adjusting	Hydraulic with pressure relief valve
Conveyor discharge height	1.5 or 1.8m	1.5 or 1.8m
Approximate weight	1,100kg with conveyor	1,500kg with conveyor
Tractor requirements power	60 - 120hp	90 - 120hp
Transmission	Creeper box or hydrostatic	Creeper box or hydrostatic
Linkage category	2 or 3	2 or 3
PTO speed	540 or 1000rpm	540 or 1000rpm

A.F.T. TRENCHERS LIMITED